

REQ	ITEM	PART NUMBER	DESCRIPTION
			LOW CARBON STEEL C1006

Ø .201 X .63 DP.
1/4-20 UNC-2B X .50 DP.
5 PLACES

⊕ Ø .014 (M) C B A

Ø .437 DIA. THRU
Ø .625 C'BORE X .50 DP.

⊕ Ø .014 (M) B A C

Ø .107 X .500 DP.
6-32 UNC-2B X .375 DP.

⊕ Ø .014 (M) B A C

Ø .422 X .80 DP.
1/2-13 UNC-2B X 1.00 DP.

⊕ Ø .014 (M) C A B

Ø .332 X 1.25 DP.
3/8-16 UNC-2B X 1.00 DP.

⊕ Ø .014 (M) B A C

Ø .275 X .56 DP.

⊕ Ø .002 (M) B A C

Ø .270 X .56 DP.

⊕ Ø .010 (M) B A C

2X Ø .2571 X .56 DP.

⊕ Ø .002 (M) B A C

NOTES: 1. ALL DIMENSIONS ARE IN INCHES.
2. APPROX. WT: 16 LBS.

					UNLESS OTHERWISE SPECIFIED		SHOP ORDERS		LAWRENCE BERKELEY LABORATORY			
					ACCT NO.		SERIAL NO.		UNIVERSITY OF CALIFORNIA-BERKELEY			
					DATE ISSD		DATE REQD		SNS - FE MEBT			
					DELIVER TO		NO. REQD		QUADRUPOLE MAGNET			
					SURFACE TREATMENT		DEGREASE		POLE PIECE - TOP			
					IDENT. METH.		TAG		PATENT CLEAR			
					DWG. BY		DATE		DWG. TYPE			
					CHK. BY		DATE		DETAIL			
					MICROFILMED		DESIGN ACCT NO.		CATEGORY CODE			
					FE3312		25B1264		F			