REQ	ITEM	PART NUMBER	DESCRIPTION
			OFE COPPER, .500 THICK PLATE

25B1414A

NOTES: 1. ALL DIMENSIONS ARE IN INCHES.

2. SILVER PLATE 0.0003/0.0005" THICK.

A1

REV	DWG	CHK	ZONE	DATE	CHANGES
A1	YM		A8	11-15-00	WAS 'FLASH GOLD' 0.00001" THK

UNLESS OTHERWISE SPECIFIED

TOLERANCES: .X ± – ; FRAC. ±1/64 ; .XX ± .02 ; ANGLES ±1° ; .XXX ± .005 ; FINISH 125√

THREADS ARE CLASS 2
CHAMFER ENDS OF ALL SCREW THREADS 30°.
CUT 1.5 PITCH THRD RELIEF WITH ROUND NOSE TOOL ON MACHINE CUT THREADS.
BREAK EDGES .016 MAX. ON MACHINED WORK
REMOVE BURRS WELD SPLATTER & LOOSE SCALE
REFERENCES: ANSI Y14.5 & B46.1.

SHOP ORDERS

ACCT NO. | SERIAL NO. | DATE ISSD | DATE REQD. | NO. REQD. | DELIVER TO

SURFACE TREATMENT: DEGREASE
IDENT. METH.: TAG
DWG. BY: Y. MINAMIHARA — DATE: 12-15-99
CHK. BY — DATE

LAWRENCE BERKELEY LABORATORY
UNIVERSITY OF CALIFORNIA-BERKELEY

SNS - FES MEBT

MECHANICAL BEAM TRANSPORT SYSTEMS - QUADS

JUMPER BAR

PATENT CLEAR	DWG. TYPE	SHOWN ON	SCALE	DO NOT SCALE PRINTS
	DETAIL		4X	
MICROFILMED	DESIGN ACCT NO.	CATEGORY CODE	DWG. NO.	SIZE / REV.
		FE3312	25B1414	A