

1. ASSEMBLE IN CLEAN ENVIRONMENT. AFTER ASSEMBLY, WRAP TO MAINTAIN CLEANLINESS.
2. FINISHED PART TO BE VACUUM TIGHT. LEAK RATE NOT TO EXCEED 1×10^{-8} torr l/sec. He.
3. DIMENSIONS IN INCHES.
4. SILVER PLATE ALL SCREWS.



```

- .98
  INSTALLED
  1.19  FREE LENGTH

```

BPM2
END

SECTION **A-A**
SPLIT FLANGE OMITTED
FOR CLARITY.

ITEM	PART NO	REQD	DESCRIPTION	MATERIAL
------	---------	------	-------------	----------

**ERNEST ORLANDO LAWRENCE
BERKELEY NATIONAL LABORATORY**
UNIVERSITY OF CALIFORNIA - BERKELEY



SNS - FES MEBT
BEAM PIPES
DETAIL ASSEMBLY, BP3 SPOOL

MICROFILMED:	DWG. TYPE	SHOWN ON	SCALE: 2/1	DO NOT SCALE PRINTS
--------------	-----------	----------	------------	---------------------

	ASSEM	25B610	SHEET 1 OF 1
--	-------	--------	---------------------

PATENT CLEAR:	DESIGN ACCT. NO.	CATEGORY CODE	DWG. NO.	SIZE	REV.
		FF3312	25B4493		C

2504493 | C