




- UNLESS OTHERWISE SPECIFIED,
- 1) DIMENSIONS AND TOLERANCING PER ASME Y14.5M-1994. ALL DIMENSIONS ARE IN INCHES. REFERENCE DIMENSIONS ARE SHOWN IN PARENTHESES. NOT ALL HIDDEN LINES ARE SHOWN.
 - 2) ALL WELDS ARE TO BE VACUUM LEAK TIGHT AND ARE TO BE HELIUM LEAK TESTED. LEEK RATE IS NOT TO EXCEED 2x 10e-9 CC/SEC He.
 - 3) THIS IS AN ULTRA HIGH VACUUM (UHV) PART AND REQUIRES SPECIAL ATTENTION TO AVOID UHV CONTAMINATION. READ LBNL SPECIFICATION M773 BEFORE PERFORMING ANY FAB- RICATION.
 - 4) PROTECT FINISHED PART BY BAGGING OR SIMILAR METHOD TO PROTECT AND MAINTAIN CLEANLINESS DURING SHIPMENT AND STORAGE. TAKE EXTREME CARE NOT TO DING, SCRATCH, DENT, OR OTHERWISE MARK ANY MACHINED SURFACE.

1	5		CONFLAT FLANGE, Ø1.33 ROTATABLE, MDC #100003
1	4	26B033	AIR GUARD SUPPLY TUBE MACHINING
1	3		BELLOWS, WELDED STAINLESS STEEL,STANDARD BELLOWS CO. #84-52-4-EE
1	2	26B029	FLANGE TO BELLOWS ADAPTER
1	1		CONFLAT FLANGE, Ø1.33 NON-ROTATABLE, MDC #110003
RECD	ITEM	PART NO.	DESCRIPTION

UNLESS OTHERWISE SPECIFIED	PROJECT NAME:	ERNEST ORLANDO LAWRENCE BERKELEY NATIONAL LABORATORY UNIVERSITY OF CALIFORNIA	
TOLERANCES X± - - XX± - - XXX± - - - FRACTIONS: * - / - - ANGLES: ± 0.5° MACH. SURFS.: 63 ✓ OR BETTER	UNIQUE NUMBER: AL-0002-7056	ALS - INSERTION DEVICE BEAMLINES	
REF:ASME Y14.5M-1994, THREADS ARE CLASS 2	DO NOT SCALE PRINT	BL 11.0.1 MONOCHROMATOR	
BREAK EDGES .016 MAX. ON MACHINED WORK	SCALE: 1 : 1	OPTIC COOLANT AIR GUARD M2 WELDMENT	
REMOVE BURRS, WELD SPLATTER & LOOSE SCALE	THIRD ANGLE PROJECTION	SHEET 1 OF 1	SIZE: D DWG NO: 26B028 REV B

REV	AUTHOR	APPROVER	DATE	CHANGE DESCRIPTION
B	patton	patton	02-13-20	CORRECT BELLOWS DESCRIPTION IN BOM
A	knolls	patton	12-19-20	INITIAL REVISION