

## Metal Oxide Resistors, Special Purpose, High Voltage



### FEATURES

- Low TC:  $\pm 200$  ppm/ $^{\circ}\text{C}$  standard;  $\pm 100$  ppm/ $^{\circ}\text{C}$ ,  $\pm 50$  ppm/ $^{\circ}\text{C}$  available
- $\pm 1\%$  standard to  $1\text{ G}\Omega$ ;  $\pm 5\%$  above  $1\text{ G}\Omega$   
 $\pm 0.5\%$  available in  $\pm 50$  ppm/ $^{\circ}\text{C}$  only. Special tolerance and/or temperature coefficient matching available.
- High Voltage type (up to  $8\text{ kV}$ )
- For oil bath or open air operation
- Matched sets available
- Special testing available upon request
- Lead (Pb)-free version is RoHS compliant



**RoHS\***  
COMPLIANT

### STANDARD ELECTRICAL SPECIFICATIONS


GLOBAL MODEL	HISTORICAL MODEL	POWER RATING			VOLTAGE RATING $V_{\equiv}$	RESISTANCE RANGE $\Omega$ <sup>(2)</sup>			
		$P_{25^{\circ}\text{C}}$ W <sup>(1)</sup>	$P_{70^{\circ}\text{C}}$ W <sup>(1)</sup>	$P_{125^{\circ}\text{C}}$ W <sup>(1)</sup>		200 ppm	100 ppm	50 ppm	NON-INDUCTIVE <sup>(3)</sup>
RNX025	RNX-1/4	0.5	0.36	0.25	750 V	1K - 100M	1K - 100M	1M - 22M	100R - 100K
RNX038	RNX-3/8	1.0	0.72	0.5	1.5 kV	1K - 1G	1K - 100M	1M - 50M	100R - 100K
RNX050	RNX-1/2	1.2	0.86	0.6	2 kV	1K - 2G	1K - 250M	1M - 100M	100R - 100K
RNX075	RNX-3/4	2.0	1.44	1.0	3 kV	1K - 2G	1K - 500M	1M - 100M	100R - 100K
RNX100	RNX-1	2.5	1.8	1.25	4 kV	1K - 2G	1K - 500M	1M - 100M	100R - 1M
RNX125	RNX-1-1/4	3.0	2.16	1.5	5 kV	1K - 2G	1K - 500M	-	100R - 1M
RNX150	RNX-1-1/2	4.0	2.88	2.0	6 kV	1K - 2G	1K - 500M	-	100R - 1M
RNX200	RNX-2	5.0	3.6	2.5	8 kV	1K - 2G	1K - 500M	-	100R - 1M

**Notes:**

- <sup>(1)</sup> Increase wattage by 25 % for 0.032" [0.813 mm] diameter leads
- <sup>(2)</sup> For resistance values above and below those listed please contact us
- <sup>(3)</sup> Non inductive  $\pm 200$  ppm/ $^{\circ}\text{C}$  TCR only
- **All resistance values are calibrated at 100 VDC. Calibration at other voltages available**
- Part Marking: print marked - DALE, model, value, tolerance, TCR, date code (model and date omitted on RNX-1/4)
- Special Modifications:
  - Special preconditioning (power aging, temperature cycling etc.) to customer specifications
  - Non-helixed resistors can be supplied for critical high frequency applications (non-inductive)

### GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: RNX05010K0KKLB (preferred part numbering format)




Historical Part Number example: RNX-1/210K0KK (will continue to be accepted)



**Notes:**

- <sup>(4)</sup> Some packaging codes are model specific
- \* Pb containing terminations are not RoHS compliant, exemptions may apply.

**DIMENSIONS**




GLOBAL MODEL	DIMENSIONS in inches [millimeters]	
	L	L <sub>1</sub> max.
RNX025	0.290 ± 0.020 [7.37 ± 0.51]	0.358 [9.09]
RNX038	0.420 ± 0.020 [10.67 ± 0.51]	0.470 [11.94]
RNX050	0.540 ± 0.020 [13.72 ± 0.51]	0.595 [15.11]
RNX075	0.790 ± 0.020 [20.07 ± 0.51]	0.845 [21.46]
RNX100	1.040 ± 0.020 [26.42 ± 0.51]	1.100 [27.81]
RNX125	1.290 ± 0.020 [32.77 ± 0.51]	1.350 [34.16]
RNX150	1.540 ± 0.020 [39.12 ± 0.51]	1.600 [40.51]
RNX200	2.040 ± 0.020 [51.82 ± 0.51]	2.100 [53.34]

**Note:**

(1) Available with 0.032" [0.813 mm] leads ± 0.002" [0.051 mm].

TECHNICAL SPECIFICATIONS									
PARAMETER	UNIT	RNX025	RNX038	RNX050	RNX075	RNX100	RNX125	RNX150	RNX200
Insulation Resistance	Ω	≥ 10 <sup>11</sup>							
Category Temperature Range	°C	- 55/+ 155							



MATERIAL SPECIFICATIONS	
<b>Element:</b>	High temperature fired cermet film
<b>Core:</b>	High purity 96 % alumina
<b>Coating:</b>	Epoxy on RNX025 and RNX038 Flameproof on RNX050 to RNX200
<b>Termination:</b>	Standard lead material is solder - coated copper. Solderable and weldable.

MECHANICAL SPECIFICATIONS	
<b>Terminal Strength:</b>	5 pound pull test
<b>Solderability:</b>	Continuous satisfactory coverage when tested in accordance with MIL-STD-202, Method 208



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.